

ANNEXURE

SL.No.	Item description: Alumina Ceramic Spacers			Qty (Nos.)
Alumina ceramic insulation spacers with following specifications: i) Color: white/Ivory ii) Alumina Content: > 90% iii) Water absorption (%): NIL iv) Dielectric strength (breakdown potential): @ 8 kV/mm v) Electrical resistivity (order of magnitude): $1 \times 10^{14} \Omega\text{-m}$ vi) Tolerances: Diameter (1.0-5.0 mm): ± 0.2 mm Diameter (5.1- 40.0 mm): ± 0.3 mm Length: (1.0-20.0 mm): ± 0.2 mm Length: (> 20.0 mm): $\pm 1\%$				
SL No.	OD(mm)	ID (mm)	Length (mm)	
1.	8.0	5.5	3.0	50 Nos
2.	8.0	5.5	5.0	50 Nos
3.	8.0	5.5	6.0	50 Nos
4.	8.0	5.5	26.0	50 Nos
5.	4.8	2.5	61.0	50 Nos
6.	5.0	3.0	2.0	50 Nos
7.	5.0	3.0	3.0	50 Nos
8.	3.0	1.8	5.6	50 Nos
Note: 1. All the items will be accepted from a single manufacturer/supplier to avoid technical/dimensional incompatibility. 2. Offers without technical specifications, catalogue and part number will not be considered.				